



The industry's first dual-phone wireless tabletop conferencing system. MAXAttach Wireless provides expanded wireless coverage for medium-sized conference rooms, delivering clear, full-duplex audio through two complete phone units – all with no cables in the way.

### HDConference Audio

- + Distributed Echo Cancellation® and noise cancellation along with full-duplex performance and automatic level controls guarantees your conference calls to be natural with unmatched audio clarity without any distractions

### Acoustic Intelligence

- + First-mic priority intelligently activates only the microphone closest to the person speaking, preventing the amplification of ambient noise and room reflections

### 360-degree Coverage

- + Three built-in microphones create array with 360-degree audio pickup within 12 feet of each conference phone. Large loudspeaker for rich, clear conferencing and audio playback

### Expandable Design

- + Daisy-chainable design can expand up to two complete phones wirelessly to cover medium-size rooms. Full conference phone expandability allows both mic and loudspeaker to cover the entire room along with flexibility of control and dialing using any conference phone



#### VENUES

Boardrooms

---

Medium Conference Rooms

---


Huddle Rooms

---

Home Office

---

Any Room Without Phone Lines



MAXAttach Wireless comes with two wireless phones that connect to a single base unit, providing expanded coverage in medium-sized rooms.

### PRODUCT SPECIFICATIONS

#### Echo Cancellation

Tail time: 60 ms x 3

#### Noise Cancellation

Dynamic noise cancellation

#### Telephone Connection

Analog PBX or PSTN line

RJ-11C, -12 dBm nominal

#### Radio

Standard DECT/DECT 6.0 (NA, Canada, LATAM)

WDCT (EMEA, APAC)

ETSI EN 300 175 1-9

#### Keypad

Alphanumeric standard keypad

#### Loudspeaker

Volume: 90 dBspl A weighted @ 1 ft

Bandwidth: 200 Hz–3.3 kHz

#### Record Output

Connector: 2.5 mm mono audio jack

Impedance: <1000 ohms

Bandwidth: 200 Hz–3.3 kHz

Dynamic range: 60 dB

THD <.01%

#### Certifications

FCC part 15/ICES-003 Class A

FCC part 15 Subpart C/RSS-210

FCC part 68/IC CS-03

CE

UL Certified

#### Power

**Phone Unit:**

Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh

12 hours continuous talk time (typical)

36 hours standby

**Base Unit:**

Auto-adjusting power module;

100-240 VAC; 50/60Hz

#### Wireless Range

DECT: 300 ft to 400 ft (91-121 m)

EU WDCT unit: 50 ft (15 m)

**Note:** These ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

#### Environmental

**Operating temperature:** 32–118° F (0–48° C)

**Storage temperature:** 41–158° F (5–70° C)

**Operating humidity:** 15 to 80%

**Storage humidity:** 10 to 90%

#### Dimensions (W x D x H)

**Phone unit:** 10.5" x 10.5" x 3"  
(26.7 cm x 26.7 cm x 7.6 cm)

**Base unit:** 4.25" x 5.5" x 2.5"  
(10.8 cm x 14 cm x 6.4 cm)

#### Weight

**Phone unit:** 2.7 lb (1.2 kg)

**Base unit:** .6 lb (0.27 kg)

**Shipping:** MAX Wireless: 10 lb (4.5 kg)

#### MAXAttach Wireless Includes Wireless phone unit (2)

Base unit (1)

Battery pack (2)

Power supply/charger (2)

Power supply retainer (2)

Telephone cable

Documentation CD

Quick start guide

#### Part Numbers

**MAXAttach**

910-158-500 (NA, Canada, LATAM)

910-158-501-00 (EMEA/APAC)

**MAXAttach Wireless**

910-158-600-00 (NA, Canada, LATAM)

910-158-601-00 (EMEA)

## SALES AND INQUIRIES

#### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116

#### US & Canada

Tel: 801.975.7200  
TollFree: 800.945.7730  
Fax: 801.303.5711

#### International

Tel: +1.801.975.7200  
global@clearone.com

#### Sales

Tel: 801.975.7200  
sales@clearone.com

#### TechSales

Tel: 801.974.3760  
techsales@clearone.com

#### TechSupport

Tel: 801.974.3760  
tech.support@clearone.com